

K-LINE 9600 SERIES CENTRE DELIVERY ROTARY RAKE



- **Clean** hay/forage sample
- **High** output (productivity)
- **Robust** & reliable
- **Oil** bathed gear boxes
- **User** friendly adjustments
- **Models** available -
Centre/side delivery &
Single rotors



Outstanding features in these rakes are:

- The only Australian-made Rotary Rake designed and produced in Australia for Australian conditions.
- Sealed oil bathed housings, protecting cams and bearings from abrasive and dusty conditions commonly known amongst Australian farmers.
- 13-arm rotors and 5 double tines per arm – This equates to 260 raking tines, effectively raking heavy crops up to 8.5m in width.
- 3-dimensional ground following - Rotary baskets are pivoted with Teflon-style DU bushes on a heavy duty under-carriage allowing the rotors to float with the contour of the ground. This results in reduced hay contamination, increased tine life and cleaner raked paddocks.
- Automatic rear steer with heavy duty flotation tyres are standard equipment, giving extra maneuverability on twin rotor rakes.
- Hydraulically adjustable rake arms - altering windrow and raking width with ease.
- Designed for safe and efficient operation



9600 CENTRE DELIVERY ROTARY RAKE SPECIFICATIONS	
OPERATING WIDTH	7.8m – 8.5m
NO OF ROTORS	2 (2@3.65m)
NO OF ARMS / ROTOR	13
TINE ACTION / ROTOR	130
GEAR BOX	Adjustable sealed oil bath Cam system
HITCHING SYSTEM	PIVOTING 3PL HEAD STOCK (CAT 2 & 3)
REAR STEERING	STANDARD AUTOMATIC
GROUND FOLLOWING ABILITY	3-DIMENSIONAL
TYRES MAIN FRAME	2X (11.5/80-15.3)
TYRES / ROTOR	4 (16X6.50-8)
MAIN FRAME WHEEL TRACK	2 POSITION
FRAME MAIN BEAM	HEAVY DUTY 250X150 RHS
<i>SPECIFICATIONS SHEET SUBJECT TO CHANGE WITHOUT PRIOR NOTICE</i>	