

# MAXXRIPPER®

THE ULTIMATE GROUND BREAKER



THE K-LINE AG MAXXRIPPER® IS THE ANSWER TO YOUR SOIL COMPACTION ISSUES



*Sustaining Farms to Sustain the World*

1800 194 131  
[www.k-line.net.au](http://www.k-line.net.au)  
[sales@k-line.net.au](mailto:sales@k-line.net.au)

# MAXXRIPPER®

Manufactured for breaking hard pans and deep tillage application, this machine has deep ripping tynes to break up compacted soils to a depth of approx. 600mm (23").

Where soil compaction is encountered, the MaxxRipper® is your answer for:

Superior root structure • Greater nutrient uptake • Better moisture availability • Healthier plant development • Higher yields

## MaxxRipper® Features

- Extremely robust frame
- Heavy duty deep-ripping tynes with shear pin system
- Heavy duty roller options for soil conditioning and clod busting
- V-pattern tyne layout for greater efficiency: gives lighter draft and better tracking ability
- Huge main frame members 250 x 150mm
- Tyne spacing – 500-550mm
- Optional range of shanks and points available
- Underframe clearance 780mm
- 7, 9 & 11 tyne models available



## MaxxRipper® Specifications

CODE	DESCRIPTION	OPERATING WIDTH APPROX.	TRACTOR POWER RANGE (hp)	WEIGHT APPROX.	TRANSPORT HEIGHT APPROX.	TRANSPORT WIDTH APPROX.	TRANSPORT LENGTH
3235T	7 Tyne Ripper, Trailing	3.5m (11.5')	280-420	4500kg (9922.5 lb)	2.1m (6.9')	3.5m (11.5')	6.95m (22.8')
3245T	9 Tyne Ripper, Trailing	4.5m (14.8')	360-500	5000kg (11025 lb)	2.1m (6.9')	4.5m (14.8')	7.32m (24.0')
3260T	11 Tyne Ripper, Trailing	6.0m (19.7')	450-600	5500kg (12127.5 lb)	2.1m (6.9')	6.0m (19.6')	7.70m (25.3')

## Point Options



### Minimum Soil Disturbance Point

Standard on all machines. Ideal for breaking that hard pan with minimal soil disturbance



### Cast Wing Point

Ideal for soil mixing and inversion